

# MATERIAL SAFETY DATA SHEET

Material Name: Moiré plaster  
Classification: Not WHMIS CONTROLLED  
WATERBASED PRODUCTS  
Material Use: Decorative Finishes Not SARA III: regulated

## Moiré Plaster

### Recommended Use:

A very finely textured tough decorative metallic shimmer type finish suitable for domestic and commercial use.

### Ingredients and CAS numbers

Acrylic copolymer emulsion	Unknown
Surfactant	Unknown
Water	7732 - 18 - 5
Micca	66402-68-4
Glass Spheres	12001-26-2
Coalescing Agents	57-55-6

### Physical characteristics:

Metallic shimmer effect  
Granular paste  
Can be coloured, please select from our colour chart or request a custom colour.  
Scuff resistant  
Easy to create multiple effects  
Washable

### Fire, Smoke & Explosive hazards

Non-combustible

### Toxicity including VOC:

46g per litre

### Skin absorption

No evidence of harmful effects from available information. If symptoms occur flush with running water and wash with soap and water. If symptoms persist seek medical attention.

**Eye absorption**

Avoid contact with eyes at all times as irritation may occur. If contact occurs, rinse eyes thoroughly with water. Seek medical attention if symptoms persist.

**Inhalation:**

If symptoms occur remove victim to fresh air.

**Ingestion**

Products are not suitable for human consumption. If consumed and if victim is alert and not convulsing, give ½ to 1 glass of water to dilute the material. Do not induce vomiting. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in vomits, rinse mouth and administer more water. Obtain medical attention.

**Packaging**

5 Litre plastic containers  
500ml plastic container sample pots.

**Disposal**

Product must be disposed of according to local regulations.  
Containers must be recycled.

**Storage**

Protect from frost storing upright in temperatures between 5 and 30 degrees C. Do not freeze.

**Mixing**

Whisk before use. Add colour tints as required.

**Coverage**

4 meters sq. per liter.

**Drying Time**

20 minutes to 1 hour, depending on film thickness.

**Application**

Varied tools such as spatulas, trowels, rollers, sponges or any tool which the artist or decorator feels will achieve a desired texture.

**Substrate**

Any interior surface suitable for regular decorating. We recommend our primer is used prior to application of any Walleffects paint product.

For more substrate information please look at our Decorative Paint Substrate document.

**Shelf Life**

2 years in original packaging.

 **T**exturline

Manufactured in Canada

335 Horner Ave Toronto M8W 1Z5

